

## Data Sheet, CR4 Battery Pack Charger

### Features

- Charges batteries for i62, d62 and d81 handsets
- Charges six batteries simultaneously
- Wall mounted
- LED charging indicator for each battery
- Internal power supply
- Easy to wipe clean



CR4 for i62 and d62



CR4 for d81

### Technical Specifications

#### Physical

Dimensions (l × w × h):	453 × 156 × 98 mm
Weight:	1.4 kg
Material:	Case: PC/ABS
Color:	Light gray

#### Functional

Supply voltage:	100-240VAC/0.7A 50/60 Hz
Charge current:	0.65 A

#### Environmental

Operating temperature:	+5°C to +40°C
Storage temperature:	-20°C to +65°C
Enclosure protection:	IP30, IEC EN 60529
Immunity to electromagnetic fields:	3 V/m, EN 301 489-6
Immunity to ESD:	4 kV contact discharge and 8 kV air discharge (EN61000-4-2)


#### Recommended cables

(not supplied by Ascom)	Power cord with IEC C13 connector
-------------------------	-----------------------------------

### **Compliance to European regulations and standards**

EU directives: R&TTE - 1999/5/EC  
Product marking:   
Safety: EN 60950-1  
EMC: EN 55022 (class B), EN 301 489-6


### **Compliance to US regulations and standards**

Product marking:   
Safety: UL 60950-1  
EMC: FCC CFR 47 Part 15

### **Compliance to Canadian regulations and standards**

Product marking:   
Safety: CSA 60950-1  
EMC: FCC CFR 47 Part 15

### **Compliance to Australian regulations and standards**

Product marking:   
Safety: IEC 60950-1  
EMC: EN 55022 (class B), EN 301 489-6

*Specifications are subject to change without notice.*